

FOWX2.E356696 - FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT - COMPONENT

Fixed Capacitors for Use in Electronic Equipment - Component

See General Information for Fixed Capacitors for Use in Electronic Equipment - Component


JYH HSU (JEC) ELECTRONICS LTD

E356696

Lu Chong Bridge Side
 Dao Hou Rd Cai Bai Country
 Dao Jiao Town
 Dongguan, Guangdong 511700 CHINA

Fixed Capacitors

| Type Dsg | Capacitor Class | Voltage Rating (V) | Capacitance (μF) (Tolerance) | Resistance | | |
|-----------|-----------------|--|---|-----------------------|-----------------|-----------------|
| | | | | for RC Devices (ohms) | Lower Temp (°C) | Upper Temp (°C) |
| JD Series | Y1/X1 | 400 Vac | from 10 pF to 4700 pF with tolerance K(+/-10%) and M(+/-20%) | — | -40 | +85/+125 |
| JY Series | Y2/X1 | 400Vac(X1) 300Vac(Y2) | from 10 pF to 10000 pF with tolerance K(+/-10%) and M(+/-20%) | — | -40 | +85/+125 |
| JD Series | Y1/X1 | 500/440/400Vac(X1) 500/440/400/250Vac(Y1) | from 10 pF to 10000 pF with tolerance K(+/-10%) and M(+/-20%) | — | -40 | +125 |
| JY Series | Y2/X1 | 500/440/400/300/250Vac(X1) 500/440/400/300/250Vac(Y2) | from 10 pF to 10000 pF with tolerance K(+/-10%) and M(+/-20%) | — | -40 | +125/105 |
| MPX | X2 | 310/305/ 300/275/250 ac | 0.0022 to 2.2 (K: +/-10%) | — | -40 | +110 |

Marking: Company name or trademark **JEC**  and type designation.

Cookies on UL

Last Updated on 2019-04-12

UL Product iQ™



FOWX8.E356696 - FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT CERTIFIED FOR CANADA - COMPONENT

Fixed Capacitors for Use in Electronic Equipment Certified for Canada - Component

See General Information for Fixed Capacitors for Use in Electronic Equipment Certified for Canada - Component

JYH HSU (JEC) ELECTRONICS LTD

Lu Chong Bridge Side
 Dao Hou Rd Cai Bai Country
 Dao Jiao Town
 Dongguan, Guangdong 511700 CHINA

E356696

Fixed Capacitors

| Type Dsg | Capacitor Class | Voltage Rating (V) | Capacitance (μF) (Tolerance) | Resistance for RC Devices (ohms) | Lower Temp (°C) | Upper Temp (°C) |
|-----------|-----------------|--|---|----------------------------------|-----------------|-----------------|
| JD Series | Y1/X1 | 400 Vac | from 10 pF to 4700 pF with tolerance K(+/-10%) and M(+/-20%) | — | -40 | +85/+125 |
| JY Series | Y2/X1 | 400Vac(X1) 300Vac(Y2) | from 10 pF to 10000 pF with tolerance K(+/-10%) and M(+/-20%) | — | -40 | +85/+125 |
| JD Series | Y1/X1 | 500/440/400Vac(X1) 500/440/400/250Vac(Y1) | from 10 pF to 10000 pF with tolerance K(+/-10%) and M(+/-20%) | — | -40 | +125 |
| JY Series | Y2/X1 | 500/440/400/300/250Vac(X1) 500/440/400/300/250Vac(Y2) | from 10 pF to 10000 pF with tolerance K(+/-10%) and M(+/-20%) | — | -40 | +125/105 |
| MPX | X2 | 310/305/ 300/275/250 ac | 0.0022 to 2.2 (K: +/-10%) | — | -40 | +110 |

Cookies on UL

Marking: Company name or trademark **JEC** type designation and the Recognized Component Mark for Canada

content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our

Last Updated on 2019-04-12